



Pruning attachment



**SkanCraft - everything
under control!**

The cultivator with rotation.

The BS tree pruning attachment is just as much a part of standard equipment for forestry services and for local communities.

The hydraulic slewing work makes it particularly simple to use our cultivator in cleared woodland and tree trimming.

Slanted grown trees or slightly oblique position of the excavator are simply balanced with the slewing and can be precisely to section.

The robust construction ensures operational safety and low wear, it is very important for municipal use and for forest holdings.



Shrubs and trees can be up to half a meter in Diameter harvested and stored sorted.



Technical Data

Type	SCK10S	SCK10	SCK15	SCK20	SCK35
Design	rigid	rotate	rotate	rotate	rotate
Weight(kg)	200	300	500	850	1700
Opening width tree holder	900	900	1000	1000	1000
Opening width scissors (mm)	400	400	450	650	900
Maximum timber diameter (mm)	220	220	250	350	500
Open/close working pressure(bar)	200	200	250	300	300
Opening / closing the quantity of oil (Liter)	50-60	50-60	60-80	80-100	150-180
Pressure rotate (bar)	-	100	100	100	100
Min. oil quantity rotate (Liter)	-	20	20	20	20
excavator weight (t)	4-10	5-10	8-15	12-20	18-35

